


ZKLF ZKLN Double Direction Axial Angular Contact Ball Bearings

ZKLF Axial angular contact ball bearings-ZKLF1560-2RS



Designation	ZKLF1560-2RS
Mass $m = \text{kg}$	0.43
Dimensions	
d -0,005	15
D -0,01	60
B -0,25	25
d1	28
r min.	0.3
r1 min.	0.6
J	46
d2	6.8
b	3
l	17
Pitch $n \times t$	$3 \times 120^\circ$
Mounting dimensions	
Da max.	35
da min.	20
t1	0.1
Fixing screws	DIN EN ISO 4762 10.9
Size	M6
$n \times t_a$	$3 \times 120^\circ$
Basic load ratings axial	
dyn. Ca N	19600
stat. C0a N	28000
Fatigue limit load Cu	1650
N	
Limiting speed nG	8200
grease min-1	
Thermally safe	3500
operating speed nP	
min-1	
Bearing frictional torque	0.2
MR Nm	
Rigidity axial caL N/ μm	400
Tilting rigidity ckL	65
Mass moment of inertia	0.102
Mm	
Axial runout μm	2
Recommended INA precision locknut	
For radial locking	ZM15
For axial locking	AM15
Tightening torque MA	10
Nm	
Required locknut force	5484
axial N	