

## Angular Contact Ball Bearing

DLR Design Super precision angular contact ball bearings -**HC71913-EDLR-T-P4S**



Designation	<b>HC71913-EDLR-T-P4S</b>
Main dimensions	
d	65
D	90
B	<b>13</b>
Basic load ratings	
Dyn. Cr(KN)	<b>13</b>
Stat. Cor( kN)	8.9
Fatigue limit load	
Cur N	680
Limiting speeds	
nG grease min	24000
nG oil min	36000
Dimensions	
r min.	<b>1</b>
r1 min.	<b>1</b>
BN	2.8
SN	7.2
SB	1.4
Contact angle	
a °	25
Mounting dimensions	
da h12	70
Da H12	85.5
ra max.	0.6
ra1 max.	0.3
Preload force FV	
L N	53
M N	160
H N	321
Lift-off force KaE	
L N	153
M N	466
H N	946
Axial rigidity ca	
L N/μm	103
M N/μm	152
H N/μm	196
Mass	
m = kg	0.19

## Spindle bearing

Spindle bearings HCB70/72/718/719..-EDLR, adjusted, matched pairs or sets, contact angle  $\alpha = 25^\circ$ , with ceramic balls, restricted tolerances, for direct oil feed via outer ring, with inserted O rings