

## Angular Contact Ball Bearing

DLR Design Super precision angular contact ball bearings -**HCB71906-EDLR-T-P4S**



Designation	<b>HCB71906-EDLR-T-P4S</b>
Main dimensions	
d	30
D	47
B	<b>9</b>
Basic load ratings	
Dyn. Cr(KN)	8.1
Stat. Cor( kN)	3.95
Fatigue limit load	
Cur N	300
Limiting speeds	
nG grease min	38000
nG oil min	60000
Dimensions	
r min.	0.3
r1 min.	0.3
BN	1.1
SN	5.3
SB	1.4
Contact angle	
a °	25
Mounting dimensions	
da h12	34
Da H12	43.5
ra max.	0.3
ra1 max.	0.15
Preload force FV	
L N	22
M N	112
H N	258
Lift-off force KaE	
L N	60
M N	322
H N	768
Axial rigidity ca	
L N/μm	52.5
M N/μm	95.1
H N/μm	132
Mass	
m = kg	0.043

## Spindle bearing

Spindle bearings HCB70/72/718/719..-EDLR, adjusted, matched pairs or sets, contact angle  $\alpha = 25^\circ$ , with ceramic balls, restricted tolerances, for direct oil feed via outer ring, with inserted O rings