

## Angular Contact Ball Bearing

DLR Design Super precision angular contact ball bearings -**HCB71914-EDLR-T-P4S**



Designation	<b>HCB71914-EDLR-T-P4S</b>
Main dimensions	
d	70
D	100
B	16
Basic load ratings	
Dyn. Cr(KN)	32.5
Stat. Cor( kN)	20.8
Fatigue limit load	
Cur N	1580
Limiting speeds	
nG grease min	17000
nG oil min	26000
Dimensions	
r min.	<b>1</b>
r1 min.	<b>1</b>
BN	3.1
SN	9.3
SB	1.4
Contact angle	
a °	25
Mounting dimensions	
da h12	76
Da H12	94.5
ra max.	0.6
ra1 max.	0.3
Preload force FV	
L N	98
M N	459
H N	1040
Lift-off force KaE	
L N	281
M N	1343
H N	3118
Axial rigidity ca	
L N/μm	126
M N/μm	218
H N/μm	298
Mass	
m = kg	0.268

## Spindle bearing

Spindle bearings HCB70/72/718/719..-EDLR, adjusted, matched pairs or sets, contact angle  $\alpha = 25^\circ$ , with ceramic balls, restricted tolerances, for direct oil feed via outer ring, with inserted O rings