

## Angular Contact Ball Bearing

DLR Design Super precision angular contact ball bearings -**XC7014-EDLR-T-P4S**



Designation	<b>XC7014-EDLR-T-P4S</b>
Main dimensions	
d	<b>70</b>
D	110
B	20
Basic load ratings	
Dyn. Cr(KN)	36
Stat. Cor( kN)	15.6
Fatigue limit load	
Cur N	1190
Limiting speeds	
nG grease min	22000
nG oil min	34000
Dimensions	
r min.	1.1
r1 min.	1.1
BN	<b>4</b>
SN	11.6
SB	1.4
Contact angle	
a °	25
Mounting dimensions	
da h12	77
Da H12	102
ra max.	<b>1</b>
ra1 max.	0.6
Preload force FV	
L N	98
M N	293
H N	587
Lift-off force KaE	
L N	280
M N	853
H N	1731
Axial rigidity ca	
L N/μm	130
M N/μm	192
H N/μm	248
Mass	
m = kg	0.596

## Spindle bearing

Spindle bearings HCB70/72/718/719..-EDLR, adjusted, matched pairs or sets, contact angle  $\alpha = 25^\circ$ , with ceramic balls, restricted tolerances, for direct oil feed via outer ring, with inserted O rings