


## ZKLF ZKLN Double Direction Axial Angular Contact Ball Bearings

### ZKLF Axial angular contact ball bearings-



Designation	ZKLF3080-2Z
Mass $m = \text{kg}$	0.78
Dimensions	
d -0,005	30
D -0,01	80
B -0,25	28
d1	45.5
r min.	0.3
r1 min.	0.6
J	63
d2	6.8
b	3
l	19
Pitch $n \times t$	$12 \times 30^\circ$
Mounting dimensions	
Da max.	53
da min.	40
t1	0.1
Fixing screws	DIN EN ISO 4762 10.9
Size	M6
$n \times t_a$	$6 \times 60^\circ$
Basic load ratings axial	
dyn. Ca N	32000
stat. C0a N	64000
Fatigue limit load $Cu$	3750
N	
Limiting speed $nG$	6700
grease min-1	
Thermally safe	4300
operating speed $nP$	
min-1	
Bearing frictional torque	0.25
MR Nm	
Rigidity axial caL N/ $\mu\text{m}$	850
Tilting rigidity ckL	300
Mass moment of inertia	0.73
Mm	
Axial runout $\mu\text{m}$	2.5
Recommended INA precision locknut	
For radial locking	ZM30
For axial locking	AM30
Tightening torque MA	32
Nm	
Required locknut force	9947
axial N	