

## GAMET Super Precision Tapered Roller Bearings

### FLANGED CUP (H TYPE) -119044x



|                          |                |
|--------------------------|----------------|
| Bearing Number           |                |
| Cone(Innenring)          | <b>119044x</b> |
| Cup(Outering)            | 119085H        |
| Dimensions               |                |
| d                        | 44.450         |
| D                        | 85.000         |
| T                        | 62.00          |
| C                        | 55.66          |
| E                        | 23.07          |
| F                        | 3.17           |
| G                        | 7.93           |
| H                        | 4.76           |
| J                        | 89.76          |
| da                       | 55             |
| L                        | 6              |
| R                        | 2.00           |
| Static Stiffness (daN/μ) |                |
| Rad.                     | 112            |
| Axi.                     | <b>9</b>       |
| Basic Rating (daN)       |                |
| Rad.                     | 2680           |
| Axi.                     | 730            |
| Speed(rpm)               |                |
| max                      | 8200           |
| Weight                   |                |
| kg                       | 1.190          |

### FLANGED CUP (H TYPE)

Double row bearings offer nearly twice the capacity of the equivalent single row bearing, and are therefore used in more heavily loaded applications.

This double row bearing has a flanged outer ring which locates the shaft axially. This can also simplify housing machining operations and overall design.

H type bearings can be pre-adjusted to give HE double row bearings. This is achieved by fitting a spacer between the inner races to give the required assembly end play or preload. The choice of setting is based upon a number of parameters such as speed, lubrication and applied loads. Spacer width is adjusted

individually prior to despatch.